

Schedule of exempt operations

| | |
|---|--|
| Name: | Mr Alex Taysum-Hunter |
| Trading name (if any): | |
| Address: | 16, Overton, Ludlow, Shropshire, England, SY8 4DY |
| Exemption Ref No: | JH0463KB |
| Address where the operation can be carried out: | 16, Overton, Ludlow, Shropshire, England, SY8 4DY |
| National Grid Reference: | SO5009171933 |

Activity Number & Description:

2 Operations

2.1 Permitted activities

2.1.1 004 - Discharge of sewage effluent in to ground of two cubic metres per day or less. First made before 6 April 2010.

2.2 The site

2.2.1 The maximum daily volume of the discharge shall be 2 cubic metres or less per day, as calculated by the method specified in the septic tank and sewage treatment plant manufacturer's and installer industry Code of Practice 'Flows and Loads 3'.

2.2.2 The sewage shall be solely domestic in origin and contain no trade effluent.

2.2.3 Prior to the discharge, the sewage must have received adequate treatment from a septic tank or sewage treatment plant designed and constructed according to the relevant British Standard design requirements in force at the time of installation.

2.2.4 The infiltration system or drainage field must have been installed in accordance with the relevant siting, design and installation requirements in force at the time of installation, including British Standard, if applicable.

2.2.5 The Discharge can only be made to a self contained infiltration system or drainage field without any observable discharge into surface waters.

2.2.6 The sewage treatment system must be installed in accordance with the manufacturer's specification issued at the time of installation or to the guidance given in the appropriate septic tank and package sewage treatment plant industry operating Code of Practice.

2.2.7 The location of the discharge must be outside a Source Protection Zone 1 and be further than 50 metres from a permitted water supply or other source of private water supply.

2.2.8 The sewage treatment system shall be operated and maintained in accordance with a maintenance plan as specified within the manufacturer's maintenance instructions or other maintenance schedule adopted by the occupier, or manufacturing industry Code of Practice guides.

2.2.9 Maintenance should be undertaken by those who are competent in respect of the responsibilities to maintain and service the sewage treatment system.

2.2.10 Waste sludge removed from the sewage treatment system must be safely disposed of in an appropriate or controlled manner, using competent disposal contractors.

2.2.11 Records demonstrating compliance with the maintenance and desludging requirements shall be in a legible format and retained for at least 5 years from the date when the records were made.

2.2.12 The discharge must not cause pollution of surface or groundwater.

2.2.13 Details of this registration and associated conditions should be stored in a safe place, and provided to next occupier on change of ownership.

Date of issue: 04/11/2010